

# INDUSTRIAL ENGINE RATINGS GUIDE



**CAT**<sup>®</sup>  
LET'S DO THE WORK.™



<b>Customer Value</b> .....	<b>4</b>
<b>Cat<sup>®</sup> Engines</b> .....	<b>5</b>
<b>EU Stage V Engines</b> .....	<b>6-12</b>
<b>U.S. EPA &amp; CARB Tier 4 Final Engines</b> .....	<b>13-18</b>
<b>China Nonroad Stage IV</b> .....	<b>19-21</b>
<b>UN ECE R96 Stage IIIA or Below</b> .....	<b>22-34</b>
<b>Basic Specifications</b> .....	<b>35-37</b>

### **Premium Engines and Components**

Able to meet the toughest challenges in the harshest conditions, Cat® engines are built to fill your needs. Easy to repair, service, and rebuild they're ready to deliver a lifetime of low-cost productivity. With Cat Finance packages we can even assist in your product purchase.

### **Aftermarket Care**

Whether you want urgent repairs and parts or just access to quality technical advise, your Cat dealer is always on hand. Our dealer network is available worldwide, offering same-day or next-day delivery and an expert team that manages every aspect of servicing and maintenance.

### **On-Site Productivity**

Reduce machine downtime and running costs to increase the productivity and profitability of your operations. We deliver the latest technology to help you stay ahead of the competition and keep your equipment running at maximum efficiency. Our goal is to make sure you get full value from your engines, right from the start.

The charts represent only a selection of the power ratings available from the Cat industrial engine range and may not yet be in full production. Other emission standards may be available. Contact your Cat dealer [www.cat.com/dealer](http://www.cat.com/dealer) for advice for your power train.

## Diesel Engine Ratings Definitions

**IND-A:** (Continuous): Continuous heavy-duty service where the engine is operated at maximum power and speed up to 100% of the time without interruption or load cycling.

**IND-B:** For service where power and/or speed are cyclic (time at full load not to exceed 80%).

**IND-C:** (Intermittent): Is the horsepower and speed capability of the engine where maximum power and/or speed are cyclic (time at full load not to exceed 50%).

**IND-D:** For service where maximum power is required for periodic overloads (time at full load not to exceed 10% of the duty cycle).

**IND-E:** For service where maximum power is required for a short time for initial starting or sudden overload. For emergency service where standard power is unavailable (time at full load not to exceed 5% of the duty cycle).

**Rating conditions for engines up to and including 7.1 liter displacement** are based on ISO/TR14396.

**Ratings for engines above 7.1 liter displacement** are based on SAEJ1995.

### Abbreviations for Engine Aspirations

NA = Naturally Aspirated

T = Turbocharged

TA = Turbocharged and Aftercooled

TTA = Twin turbocharged and Aftercooled

### Abbreviations for Aftertreatment

DOC = Diesel Oxidation Catalyst

DPF = Diesel Particulate Filter

SCR = Selective Catalytic Reduction

Information is subject to change without notification.

## EU Stage V

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
0.51	C0.5	2	NA	8.8 (11.8)	3000	30 (22)	2100	–	C	
0.76	C0.7	3	NA	9 (12.1)	2200	40 (30)	1800	–	C	
				12.2 (16.4)	2800	45 (33)	2000			
				13.3 (17.8)	3600	44 (32)	2400			
1.1	C1.1	3	NA	14.7 (19.7)	2200	67 (49)	2100	–	C	Y
				16.1 (22)	2400	67 (49)	2100			
				18.4 (25)	2800	67 (49)	2100			
				18.9 (25)	2800	69 (51)	2100			
			T	18.4 (25)	2800	86 (63)	1600			
				18.9 (25)	2800	86 (63)	1600			

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit	
1.7	C1.7	3	NA	18.4 (25)	2800	85 (63)	1800	-	C		
				18.4 (25)	2200	92 (68)	1600				
				18.9 (25)	2800	87 (64)	1800				
				18.9 (25)	2200	98 (72)	1400				
			T	17.7 (24)	2200	100 (74)	1600				
				18.2 (24)	2200	103 (76)	1600				
				18.4 (25)	2800	90 (66)	1800				
				18.9 (25)	2800	92 (68)	1800				
				36 (48)	2800	166 (122)	1400				DOC+DPF
2.2	C2.2	4	T	36 (48)	2800	190 (140)	1600	DOC+DPF	C		
				45 (60)	2800	222 (164)	1600				
			TA	45 (60)	2800	235 (173)	1600				
				50 (67)	2800	252 (186)	1600				
				55 (74)	2800	270 (199)	1600				

## EU Stage V

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
2.8	C2.8	4	T	50 (67)	2200-2400	265 (195)	1600	DOC+DPF	C	
				55 (74)	2200-2400	265 (195)	1600			
				55 (74)	2200-2400	300 (221)	1600			
			TA	55 (74)	2200-2400	380 (280)	1380			
3.6	C3.6	4	TA	55 (74)	2200-2400	424 (313)	1200	DOC+DPF	C	
				70 (94)	2200-2400	450 (332)	1500	DOC+DPF+SCR		
				90 (121)	2000-2400	500 (369)	1500			
				95 (127)	2000-2400	530 (391)	1500			
				100 (134)	2000-2200	550 (406)	1500		D	



Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
4.4	C4.4	4	TA	82 (110)	2000-2200	450 (332)	1400	DOC+DPF+SCR	C	
				98 (131)	2000-2200	530 (391)	1400			
				102 (137)	2000-2200	560 (413)	1400			Y
				106 (142)	2000-2200	560 (413)	1400			
				110 (148)	2000-2200	560 (413)	1400			
			TTA	105 (141)	2000-2200	750 (553)	1400			
				112 (150)	2000-2200	750 (553)	1400			
				129 (173)	2000-2200	750 (553)	1400		Y	
				140 (188)	1800-2000	825 (609)	1400			
				150 (201)	2200	825 (609)	1400		D	

## EU Stage V

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
7	C7.1	6	TA	129 (173)	1800-2200	842 (621)	1400	DOC+DPF+SCR	C	Y
				151 (202)	1800-2200	908 (670)	1400			
			TTA	151 (202)	1800-2200	983 (725)	1400			
				186 (249)	1800-2200	1214 (895)	1400			
				205 (275)	1800-2200	1257 (927)	1400			
				225 (302)	1800-2200	1274 (940)	1400			
				239 (320)	1800	1282 (946)	1400		D	
9.3	C9.3B	6	TA	250 (335)	1800-2200	1537 (1134)	1400	DOC+DPF+SCR	A	Y
				280 (375)	1800-2200	1721 (1269)	1400		B	
				310 (416)	1800-2200	1904 (1404)	1400		C	
				340 (456)	1800-2000	2088 (1540)	1400		D	

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
12.5	C13B	6	TA	340 (456)	1800-2100	2082 (1536)	1400	DOC+DPF+SCR	A	Y
				370 (496)	1800-2100	2266 (1671)	1400		B	
				400 (536)	1800-2100	2450 (1807)	1400		C	
				430 (577)	1800-2100	2634 (1943)	1400		D	
15.2	C15	6	TA	354 (475)	1800-2100	2174 (1603)	1400	DOC+DPF+SCR	A	Y
				354 (475)	1800-2100	2174 (1603)	1400		B	
				403 (540)	1800-2100	2472 (1823)	1400		C	
				433 (580)	1800-2100	2655 (1958)	1400		D	
18.1	C18	6	TA	429 (575)	1800-2000	2694 (1987)	1300	DOC+DPF+SCR	A	Y
				447 (599)	1800-2000	2811 (2073)	1300		B	
				470 (630)	1800-2000	2951 (2177)	1300		C	
			TTA	563 (755)	1800	3501 (2582)	1300	DOC	D	
				597 (800)	1800	3710 (2736)	1300			

## EU Stage V

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
27	C27	12	TA	597 (800)	1800	3676 (2711)	1200	DOC	A	Y
				653 (875)	1800	3984 (2939)	1200		B	
				709 (950)	1800	4354 (3211)	1200		C	
				783 (1050)	1800	4679 (3451)	1200		D	
32	C32	12	TA	746 (1000)	1800	5186 (3825)	1200	DOC	B	Y
				839 (1125)	1800	5499 (4056)	1200		C	
78	3516E	16	TA	1566 (2100)	1650	11220 (8275)	1200	SCR	A	

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit		
0.76	C0.7	3	NA	8.8 (11.8)	2200	41 (30)	1800	-	C			
1.1	C1.1	3	NA	14.7 (19.7)	2200	67 (49)	2100	-	C	Y		
				16.1 (22)	2400	67 (49)	2100					
				18.4 (25)	2800	67 (49)	2100					
			T	18.4 (25)	2800	86 (63)	1600					
1.7	C1.7	3	NA	18.4 (25)	2800	85 (63)	1800	-	C			
				18.4 (25)	2200	92 (68)	1600					
			T	17.7 (24)	2200	100 (74)	1600					
				18.4 (25)	2800	90 (66)	1800					
				30 (40)	2800	125 (92)	1800				DOC	Y
				36 (48)	2800	166 (122)	1400				DOC+DPF	

## U.S. EPA & CARB Tier 4 Final

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
2.2	C2.2	4	T	36 (48)	2800	165 (122)	1800	DOC	C	Y
				36 (48)	2800	190 (140)	1600	DOC+DPF		
				45 (60)	2800	222 (164)	1600			
			TA	45 (60)	2800	235 (173)	1600			
				50 (67)	2800	252 (186)	1600			
				55 (74)	2800	270 (199)	1600			
2.8	C2.8	4	T	50 (67)	2200-2400	265 (195)	1600	DOC or DOC+DPF	C	
				55 (74)	2200-2400	265 (195)	1600			
				55 (74)	2200-2400	300 (221)	1600			
			TA	55 (74)	2200-2400	380 (280)	1380	DOC+DPF		

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit	
3.6	C3.6	4	TA	55 (74)	2200-2400	424 (313)	1200	DOC+DPF	C		
				70 (94)	2200-2400	450 (332)	1500				
				90 (121)	2000-2400	500 (369)	1500	DOC+DPF+SCR			D
				95 (127)	2000-2400	530 (391)	1500				
				100 (134)	2000-2200	550 (406)	1500				
4.4	C4.4	4	TA	82 (110)	2000-2200	450 (332)	1400	DOC+DPF+SCR	C	Y	
				98 (131)	2000-2200	530 (391)	1400				
				102 (137)	2000-2200	560 (413)	1400				
				106 (142)	2000-2200	560 (413)	1400				
				110 (148)	2000-2200	560 (413)	1400				
			TTA	105 (141)	2000-2200	750 (553)	1400			Y	
				112 (150)	2000-2200	750 (553)	1400				
				129 (173)	2000-2200	750 (553)	1400				
				140 (188)	1800-2000	825 (609)	1400				
				150 (201)	2200	825 (609)	1400				D

## U.S. EPA & CARB Tier 4 Final

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
7	C7.1	6	TA	129 (173)	1800-2200	842 (621)	1400	DOC+DPF+SCR	C	Y
				151 (202)	1800-2200	908 (670)	1400			
			TTA	151 (202)	1800-2200	983 (725)	1400			
				186 (249)	1800-2200	1214 (895)	1400			
				205 (275)	1800-2200	1257 (927)	1400			
				225 (302)	1800-2200	1274 (940)	1400			
				239 (320)	1800	1282 (946)	1400		D	
9.3	C9.3B	6	TA	250 (335)	1800-2200	1537 (1134)	1400	DOC+DPF+SCR	A	Y
				280 (375)	1800-2200	1721 (1269)	1400		B	
				310 (416)	1800-2200	1904 (1404)	1400		C	
				340 (456)	1800-2000	2088 (1540)	1400		D	



Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
12.5	C13B	6	TA	340 (456)	1800-2100	2082 (1536)	1400	DOC+DPF+SCR	A	Y
				370 (496)	1800-2100	2266 (1671)	1400		B	
				400 (536)	1800-2100	2450 (1807)	1400		C	
				430 (577)	1800-2100	2634 (1943)	1400		D	
15.2	C15	6	TA	354 (475)	1800-2100	2174 (1603)	1400	DOC+DPF+SCR	A	Y
				354 (475)	1800-2100	2174 (1603)	1400		B	
				403 (540)	1800-2100	2472 (1823)	1400		C	
				433 (580)	1800-2100	2655 (1958)	1400		D	
18.1	C18	6	TA	429 (575)	1800-2000	2694 (1987)	1300	DOC+DPF+SCR	A	Y
				447 (599)	1800-2000	2811 (2073)	1300		B	
				470 (630)	1800-2000	2951 (2177)	1300		C	
			TTA	563 (755)	1800	3501 (2582)	1300	DOC	D	
				597 (800)	1800	3710 (2736)	1300			

## U.S. EPA & CARB Tier 4 Final

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
27	C27	12	TA	597 (800)	1800	3676 (2711)	1200	DOC	A	Y
				653 (875)	1800	3984 (2939)	1200		B	
				709 (950)	1800	4354 (3211)	1200		C	
				783 (1050)	1800	4679 (3451)	1200		D	
32	C32	12	TA	746 (1000)	1800	5186 (3825)	1200	DOC	B	Y
				839 (1125)	1800	5499 (4056)	1200		C	
				895 (1200)	1800	5861 (4323)	1200		D	
78	3516E	16	TA	1566 (2100)	1650	11220 (8275)	1200	SCR	A	

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
1.1	C1.1	3	NA	16.1 (22)	2400	68 (50)	2100	-	C	
				18.4 (25)	2800	64 (47)	2100			
				18.4 (25)	2800	68 (50)	2100			
			21 (28)	3400	70 (52)	2400				
			T	18.4 (25)	2400	86 (63)	1600			
1.7	C1.7	3	NA	18.9 (25)	2200	98 (72)	1400	-	C	
2.2	C2.2	4	NA	34 (46)	2400	141 (104)	1800	-	C	
				36 (48)	2800	140 (103)	1800			
				36 (48)	2800	143 (105)	1800			
			T	36 (48)	2500	190 (140)	1700			
3.6	C3.6	4	TA	74 (99)	2200	430 (317)	1500	DOC+DPF	C	
				82 (110)	2200	450 (332)	1500			

## China Nonroad Stage IV

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
4.4	C4.4	4	TA	110 (148)	2000	560 (413)	1400	DOC+DPF	C	
			TTA	112 (150)	2200	650 (479)	1400			
				117 (157)	1900-2200	730 (538)	1400			
				129 (173)	1900-2200	750 (553)	1400			
7	C7.1	6	TA	130 (174)	1800-2200	842 (621)	1400	DOC+DPF+SCR	C	
				151 (202)	1800-2200	870 (642)	1400			
			TTA	151 (202)	1800-2200	983 (725)	1400			
				168 (225)	1800-2200	1092 (805)	1400			
				186 (249)	1800-2200	1214 (895)	1400			
				205 (275)	1800-2200	1257 (927)	1400			
				225 (302)	2000-2200	1274 (940)	1400			
9.3	C9.3B	6	TA	250 (335)	1800-2200	1530 (1129)	1400	DOC+DPF+SCR	A	Y
				280 (375)	1800-2200	1714 (1264)	1400		B	
				310 (416)	1800-2200	1897 (1399)	1400		C	
				340 (456)	1800	2088 (1540)	1400		D	

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N·m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
12.5	C13B	6	TA	340 (456)	1800-2100	2082 (1536)	1400	DOC+DPF+SCR	A	Y
				370 (496)	1800-2100	2266 (1671)	1400		B	
				400 (536)	1800-2100	2450 (1807)	1400		C	
				430 (577)	1800-2100	2634 (1943)	1400		D	
15.2	C15	6	TA	354 (475)	1800-2100	2174 (1603)	1400	DOC+DPF+SCR	A	Y
				354 (475)	1800-2100	2174 (1603)	1400		B	
				403 (540)	1800-2100	2472 (1823)	1400		C	
				433 (580)	1800-2100	2655 (1958)	1400		D	
18.1	C18	6	TA	429 (575)	1800-2000	2694 (1987)	1300	DOC+DPF+SCR	A	Y
				447 (599)	1800-2000	2811 (2073)	1300		B	
				470 (630)	1800-2000	2951 (2177)	1300		C	

## UN ECE R96 Stage IIIA or Below

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
0.51	C0.5	2	NA	8.2 (11)	2800	30 (22)	2100	-	C	
				10.2 (13.7)	3600	30 (22)	2600			
0.76	C0.7	3	NA	15.3 (21)	3600	50 (37)	2400	-	C	
1.1	C1.1	3	NA	17.3 (23)	2600	67 (49)	2100	-	C	Y
				19.7 (26)	3000	67 (49)	2100			
				21 (28)	3400	67 (49)	2400			
1.5	C1.5	3	NA	22 (30)	2400	96 (71)	1800	-	C	Y
				23 (31)	2600	96 (71)	1800			
				24 (32)	2800	96 (71)	1800			
				25 (34)	3000	96 (71)	1800			
				23 (31)	2200	112 (83)	1800			
			T	25 (34)	2400	112 (83)	1800			
				27 (36)	2600	112 (83)	1800			
				29 (39)	2800	112 (83)	1800			
				30 (40)	3000	112 (83)	1800			

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
1.7	C1.7	3	NA	24 (32)	2400	105 (77)	1800	-	C	
2.2	C2.2	4	NA	31 (42)	2200	143 (105)	1800	-	C	Y
				36 (48)	2600	143 (105)	1800			
				37 (50)	2800	143 (105)	1800			
				38 (51)	3000	143 (105)	1800			
			T	36 (48)	2800	190 (140)	1700			
				40 (54)	2600	189 (139)	1800			
				43 (58)	2600	189 (139)	1800			
				45 (60)	2800	189 (139)	1800			
				46 (62)	3000	189 (139)	1800			
			TA	49 (66)	2800	200 (148)	1800			

## UN ECE R96 Stage IIIA or Below

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
2.8	C2.8	4	T	50 (67)	2200-2400	265 (195)	1600	-	C	
				55 (74)	2200-2400	265 (195)	1600			
				55 (74)	2200-2400	300 (221)	1600			
3.6	C3.6	4	TA	55 (74)	2200-2400	424 (313)	1200	-	C	
				70 (94)	2200-2400	450 (332)	1500			
				82 (110)	2000-2400	500 (369)	1500			
				86 (115)	2000-2400	500 (369)	1500			
				90 (121)	2000-2400	500 (369)	1500			



Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
4.4	3054	4	TA	97 (130)	2200	500 (369)	1400	-	C	Y
			NA	56 (75)	2200	265 (195)	1700			
			T	75 (101)	2200	392 (289)	1400			Y
			TA	83 (111)	2200	418 (308)	1400			
	C4.4		T	75 (101)	2200	420 (310)	1400			
			TA	75 (101)	2200	441 (325)	1400			Y
				82 (110)	2200	486 (358)	1400			
				87 (117)	2200	516 (381)	1400			
				97 (130)	2200	516 (381)	1400			
				106 (142)	2200	558 (412)	1400			

## UN ECE R96 Stage IIIA or Below

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
7	C7.1	6	TA	112 (150)	1950	687 (507)	1200	-	C	Y
				129 (173)	2200	733 (541)	1400			
				162 (217)	2200	900 (664)	1400			
				112 (150)	2200	672 (496)	1100			
				117 (157)	2200	706 (521)	1400			
				129 (173)	2500	695 (513)	1400			
				168 (225)	2200	1028 (758)	1400			
				186 (249)	2200	1050 (774)	1400			
				205 (275)	2200	1050 (774)	1400			
7.2	C7	6	TA	172 (231)	1800-2200	924 (682)	1650	-	B	
				186 (249)	1800-2200	1142 (842)	1400		C	
				205 (275)	1800-2200	1257 (927)	1400		D	
				223 (299)	2100-2200	1275 (940)	1400			

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
9.3	C9.3B	6	TA	230 (308)	1800-2200	1416 (1044)	1400	-	A	Y
				250 (335)	1800-2200	1532 (1130)	1400		B	
				280 (375)	1800-2000	1715 (1265)	1400		C	
				310 (416)	1800-1900	1810 (1335)	1400			
11.1	C11	6	TA	242 (325)	1800-2100	1487 (1097)	1400	-	A	Y
				261 (350)	1800-2100	1596 (1177)	1400		B	
				287 (385)	1800-2100	1760 (1298)	1400		C	
				313 (420)	1800-2100	1919 (1415)	1400		D	
				336 (451)	1800-2100	2056 (1517)	1400		E	
12.5	C13	6	TA	287 (385)	1800-2100	1760 (1298)	1400	-	A	Y
				328 (440)	1800-2100	2011 (1483)	1400		C	
				385 (516)	1800	2364 (1744)	1400			
				388 (520)	1800-2100	2215 (1634)	1400		E	Y
				400 (536)	1800-2000	2122 (1565)	1800		C	

## UN ECE R96 Stage IIIA or Below

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
14.6	3406C	6	TA	269 (361)	1800	1696 (1251)	1200	-	A	Y
				328 (440)	2000	1920 (1416)	1400		B	
				343 (460)	2100	1989 (1467)	1400		C	
				347 (465)	1800	2172 (1602)	1350		D	
	3406C Fire Pump			218 (292)	1750	-	-		-	-
				321 (430)	2100	-	-			
				343 (460)	1750	-	-			
				339 (455)	2300	-	-			
				359 (481)	2100	-	-			
15.2	C15	6	TA	354 (475)	1800-2100	2171 (1601)	1400	-	B	Y
				403 (540)	1800-2100	2464 (1817)	1400		C	
				433 (580)	1800-2100	2649 (1954)	1400		D	
				444 (595)	1800-2100	2719 (2005)	1400		E	

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
18.1	C18	6	TTA	571 (765)	1800-2100	3495 (2578)	1400	-	D	
				597 (800)	1800-2100	3655 (2696)	1400		E	
			TA	429 (575)	1800-2100	2627 (1938)	1400		A	Y
				448 (600)	1800-2100	2742 (2022)	1400		B	
				470 (630)	1800-2100	2768 (2042)	1400		C	
	TTA		522 (700)	1800-2100	3201 (2361)	1400				
	C18 Fire Pump		TA	447 (599)	1750-2100	-	-		-	
				522 (700)	1500-2100	-	-			
				597 (800)	1750-2100	-	-			

## UN ECE R96 Stage IIIA or Below

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
27	C27	12	TA	597 (800)	1800-2100	3657 (2697)	1400	-	A	Y
				653 (875)	1800-2100	4000 (2950)	1400		B	
				709 (950)	1800-2100	4322 (3188)	1400		C	
				783 (1050)	1800-2100	4798 (3539)	1400		D	
	858 (1150)			1800-2100	5255 (3876)	1400	E			
	3412			465 (624)	1800	2757 (2034)	1300		A	
	3412C Fire Pump			540 (724)	2100	2971 (2191)	1400		C	
				476 (638)	1750	-	-		-	
				551 (739)	1900-2100	-	-		-	
32	C32	12	TA	709 (950)	1800-2100	4338 (3200)	1400	-	B	Y
				839 (1125)	1800-2100	5143 (3793)	1400		C	
				895 (1200)	1800-2100	5484 (4045)	1400		D	
				1007 (1350)	1800-2100	6166 (4548)	1400		E	

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
34.5	3508	8	TA	470 (630)	1100	3794 (2798)	1100	-	A	
				507 (680)	1200	4156 (3065)	1000			
				578 (775)	1800	3180 (2346)	1400			
				637 (854)	1800	3585 (2644)	1400			
				746 (1000)	1800	4263 (3144)	1450			
	3508 Fire Pump			709 (951)	1460	-	-		-	
				794 (1065)	1750	-	-		-	
	3508B			746 (1000)	1800	4353 (3211)	1450		A	
				783 (1050)	1800	4569 (3370)	1450		B	
				820 (1100)	1800	4353 (3211)	1450		C	

## UN ECE R96 Stage IIIA or Below

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
51.8	3512	12	TA	761 (1021)	1200	6188 (4564)	1400	-	A	
				858 (1151)	1300	6488 (4786)	1000		C	
				955 (1281)	1800	5114 (3772)	1400		A	
				1119 (1501)	1800	6210 (4580)	1400		C	
	3512 Fire Pump			1066 (1430)	1460	-	-		-	
				1193 (1600)	1750	-	-		-	
	3512B			1119 (1501)	1800	6526 (4814)	1450		A	
				1174 (1574)	1800	6854 (5056)	1450		B	
				1230 (1649)	1800	7180 (5296)	1450		C	
58.6	3512C	12	TA	1120 (1502)	1800	7130 (5259)	1500	-	A	



Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
69	3516	16	TA	1011 (1356)	1200	8282 (6109)	1000	-	A	
				1242 (1666)	1300	9211 (6794)	1000		C	
				1275 (1710)	1800	7032 (5187)	1400		A	
				1492 (2001)	1800	8391 (6189)	1400		C	
	3516 Fire Pump			1417 (1900)	1460	-	-		-	
	1480 (1985)			1750	-	-	-			
78	3516C	16	TA	1566 (2100)	1750	10254 (7563)	1300	-	A	
110.8	3606	6	TA	1490 (1998)	750	19540 (14413)	615	-	A	
				1640 (2199)	750	21508 (15864)	615		C	
				1782 (2390)	900	19286 (14225)	720		A	
				1850 (2481)	1000	18200 (13424)	820			
				2150 (2883)	1000	21150 (15600)	820		C	

## UN ECE R96 Stage IIIA or Below

Liters	Model	Cylinders	Aspiration	Power kW (hp)	Rated Speed rpm	Maximum Torque N•m (lb-ft)	Maximum Torque Speed rpm	Aftertreatment	Rating Type	Available as a Power Unit
147.8	3608	8	TA	2088 (2800)	800	25670 (18934)	656	-	A	
				2300 (3084)	900	25136 (18540)	720		C	
				2574 (3452)	900	28950 (21354)	738		A	
				2460 (3299)	1000	24700 (18219)	820		C	
				2710 (3634)	1000	26660 (19664)	820			
221.7	3612	12	TA	2970 (3983)	750	38950 (28730)	675	-	A	
295.6	3612	12	TA	3135 (4204)	900	33729 (24879)	720	-	A	
				3460 (4640)	900	37810 (27889)	790		C	
				3800 (5096)	900	41530 (30633)	800			
				4252 (5702)	1000	41822 (30848)	800			
	3616	16		4050 (5431)	765	56061 (41351)	650		A	
				4600 (6169)	900	50270 (37079)	738		C	
				5060 (6785)	900	55300 (40789)	820		A	
				4920 (6598)	1000	48390 (35692)	820		C	
				5700 (7644)	1000	56900 (41969)	820			

All of our engines are offered with a choice of factory configurable options. The weight and dimensions will depend on the final configuration selected to match your machine. The figures in this table are therefore indicative only, and do not include aftertreatment.

<b>Model</b>	<b>Bore mm (in)</b>	<b>Stroke mm (in)</b>	<b>Length mm (in) Front of Crank Pulley to Rear Face of Flywheel Housing</b>	<b>Width mm (in)</b>	<b>Height mm (in)</b>	<b>Dry Weight kg (lbs)</b>
C0.5	67 (2.6)	72 (2.8)	407 (16)	371 (14.6)	523 (20.6)	57 (126)
C0.7	67 (2.6)	72 (2.8)	480 (18.9)	371 (14.6)	528 (20.8)	71 (157)
C1.1	77 (3)	81 (3.2)	491 (19.3)	400 (15.7)	576 (22.7)	96 (212)
C1.5	84 (3.3)	90 (3.5)	572 (22.5)	541 (21.3)	643 (25.3)	156.5 (345)
C1.7	84 (3.3)	100 (3.9)	572 (22.5)	453 (17.8)	643 (25.3)	158 (348)
C2.2	84 (3.3)	100 (3.9)	661 (26)	464 (18.3)	676 (26.6)	184 (406)
C2.8	90 (3.5)	110 (4.3)	633.1 (24.9)	542.5 (21.4)	785.5 (30.9)	320 (706)
C3.6	98 (3.9)	120 (4.7)	667 (26.3)	564 (22.2)	787 (31)	372 (820)
3054	105 (4.1)	127 (5)	663 (26.1)	620 (24.4)	775 (30.5)	306 (675)
C4.4	105 (4.1)	127 (5)	631 (24.8)	626 (24.6)	958 (37.7)	360 (794)
C7.1	105 (4.1)	135 (5.3)	1074 (42.3)	721 (28.4)	824 (32.4)	704 (1552)

## Basic Specifications

<b>Model</b>	<b>Bore mm (in)</b>	<b>Stroke mm (in)</b>	<b>Length mm (in) Front of Crank Pulley to Rear Face of Flywheel Housing</b>	<b>Width mm (in)</b>	<b>Height mm (in)</b>	<b>Dry Weight kg (lbs)</b>
C7	110 (4.3)	127 (5)	1053 (41.5)	758 (29.8)	1032 (40.6)	588 (1297)
C9.3B	115 (4.5)	149 (5.9)	1125 (44.3)	791 (31.1)	1068 (42)	865 (1907)
C11	130 (5.1)	140 (5.5)	1203 (47.4)	1054 (41.5)	1186 (46.7)	1138 (2509)
C13B	130 (5.1)	157 (6.2)	1274 (50.2)	994 (39.1)	1134 (44.6)	1125 (2481)
3406C	137.2 (5.4)	165.1 (6.5)	1660 (65.4)	906 (35.7)	1335 (52.6)	1300 (2866)
C15	137 (5.4)	171 (6.7)	1438 (56.6)	969 (38.1)	1248 (49.1)	1542 (3400)
C18	145 (5.7)	183 (7.2)	1438 (56.6)	943 (37.1)	1239 (48.8)	1542 (3400)
C18 Fire Pump	145 (5.7)	183 (7.2)	1453 (57.2)	999 (39.3)	1263 (49.7)	1673 (3689)
C27	137 (5.4)	152 (6)	1874 (73.8)	1600 (63)	1370 (53.9)	3004 (6624)
3412	137.2 (5.4)	152.4 (6)	1660 (65.4)	906 (35.7)	1335 (52.6)	1300 (2866)
C32	145 (5.7)	162 (6.4)	1874 (73.8)	1600 (63)	1370 (53.9)	3004 (6624)

<b>Model</b>	<b>Bore mm (in)</b>	<b>Stroke mm (in)</b>	<b>Length mm (in) Front of Crank Pulley to Rear Face of Flywheel Housing</b>	<b>Width mm (in)</b>	<b>Height mm (in)</b>	<b>Dry Weight kg (lbs)</b>
3508B	170 (6.7)	190 (7.5)	2136 (84.1)	1703 (67)	1720 (67.7)	4309 (9501)
3512	170 (6.7)	190 (7.5)	2676 (105)	1703 (67)	1720 (67.7)	6078 (13402)
3512B	170 (6.7)	190 (7.5)	3067 (121)	1785 (70.3)	1806 (71.1)	6078 (13402)
3512C	170 (6.7)	215 (8.5)	3067 (121)	1785 (70.3)	1806 (71.1)	6078 (13402)
3516	170 (6.7)	190 (7.5)	3366 (133)	1703 (67)	1720 (67.7)	7484 (16502)
3516C	170 (6.7)	215 (8.5)	3278 (129)	1530 (60.2)	2062 (81.2)	7840 (17287)
3516E	170 (6.7)	215 (8.5)	3105 (122)	1616 (63.6)	2108 (83)	8176 (18028)
3606	280 (11)	300 (11.8)	3988 (157)	1748 (68.8)	2626 (103)	15680 (34574)
3608	280 (11)	300 (11.8)	4828 (190)	1748 (68.8)	2626 (103)	19000 (41895)
3612	280 (11)	300 (11.8)	4562 (180)	1704 (67.1)	3231 (127)	25140 (55434)

## Notes

---

---

---

---

---

---

---

---

---

---

---



# Caterpillar. Your Local Resource. Worldwide.

Your Cat dealer can answer any questions you have about Cat Power Systems, customer support, parts, or service capability anywhere in the world. To find your local Cat dealer, visit our website [www.cat.com/dealer](http://www.cat.com/dealer).

Caterpillar Customer Interaction Center  
501 Southwest Jefferson Avenue  
Peoria, IL 61630 USA

Tel. (888) 614-4328 toll free in United States and Canada

Tel. +1 (309) 675-2337 International

Materials and specifications are subject to change without notice. Rating ranges listed include the lowest and highest available for a specific engine or family of engines. Load factor and time at rated load and speed will determine the best engine/rating match.

LEGH0002-13 (2-21)

© 2021 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Yellow", the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

