

## CAT 3412C Generator Set

<https://www.zepelin-powersystems.com/de/en/>



Minimum Rating	635 ekW
Maximum Rating	800 ekW
Emissions/Fuel Strategy	Low Fuel Consumption
Voltage	220 to 480 Volts
Frequency	60 Hz
Speed	1800 rpm
Duty Cycle	Standby, Prime
Engine Model	3412C TA, V-12, 4-Stroke Water-Cooled Diesel
Bore	137,2 mm
Stroke	152,4 mm
Displacement	27,02 l
Compression Ratio	13:00:01
Aspiration	TA
Fuel System	Pump and Lines
Governor Type	ADEM™ A5
Length - Maximum	4.125 mm
Width - Maximum	1.989 mm
Height - Maximum	1.906 mm
Dry Weight - Genset (minimum)	12.700 kg
Dry Weight - Genset (maximum)	6.021 kg
Maximum Rating	800 kVA
Minimum Rating	635 kVA
Rated Speed	1800 rpm

This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.

**CAT 3412C Generator Set**

