

CAT 3412C Generator Set

https://www.zeppelin-powersystems.com/de/en/



Minimum Rating 680 kVA Maximum Rating 900 kVA

Emissions/Fuel Strategy Low Fuel Consumption Voltage 380 to 415 Volts

Frequency 50 Hz
Speed 1500 rpm
Duty Cycle Standby, Prime

Engine Model 3412C TA, V-12, 4-Stroke Water-Cooled Diesel

Bore 137,2 mm
Stroke 152,4 mm
Displacement 27,02 I
Compression Ratio 13:01
Aspiration TA

Pump and Lines Fuel System Governor Type ADEM™ A5 Length - Maximum 4.125 mm Width - Minimum 1.906 mm Width - Maximum 1.989 mm Height - Maximum 1.906 mm Dry Weight - Genset (minimum) 5.461 kg Dry Weight - Genset (maximum) 5.910 kg Maximum Rating 900 kVA 680 kVA Minimum Rating Rated Speed 1500 rpm

This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.



CAT 3412C Generator Set





