

## CAT 3512B Diesel Generator Set

<https://www.zepelin-powersystems.com/de/en/>



Minimum Rating	1320 kVA
Maximum Rating	1750 kVA
Emissions/Fuel Strategy	Low Fuel , Low Emissions
Voltage	400 to 415 Volts
Frequency	50 Hz
Speed	1500 rpm
Duty Cycle	Standby, Mission Critical, Prime, Continuous
Engine Model	3512B TA, V-12, 4-Stroke Water-Cooled Diesel
Bore	170 mm
Stroke	190 mm
Stroke - HD	215 mm
Displacement	52,8 l
Displacement - HD	58,56 l
Compression Ratio	14.0:1 Std 15.5:1 HD
Aspiration	TA
Fuel System	Electronic Unit Injection
Governor Type	ADEM™A3
Length - Minimum	5.404 mm
Length - Maximum	5.515 mm
Width - Minimum	2.286 mm
Width - Maximum	2.286 mm
Height - Minimum	2.411 mm
Height - Maximum	2.411 mm
Dry Weight - Genset (minimum)	11.621 kg
Dry Weight - Genset (maximum)	12.034 kg
Maximum Rating	1.750 kVA
Minimum Rating	1.320 kVA
Rated Speed	1500 rpm



## CAT 3512B Diesel Generator Set

This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.

**CAT 3512B Diesel Generator Set**

