

CAT 3512B Diesel Generator Set

<https://www.zepelin-powersystems.com/de/en/>



Minimum Rating	1230 ekW
Maximum Rating	1500 ekW
Emissions/Fuel Strategy	Low Fuel, Low Emissions
Voltage	380 to 13800 Volts
Frequency	60 Hz
Speed	1800 rpm
Duty Cycle	Standby, Mission Critical, Prime, Continuous
Engine Model	3512B TA, V-12, 4-Stroke Water-Cooled Diesel
Bore	170 mm
Stroke	190 mm
Displacement	58,56 l
Compression Ratio	14.0:1 Std 15.5:1 HD
Aspiration	TA
Fuel System	Electronic Unit Injection
Governor Type	Adem™3
Length - Maximum	5.637,5 mm
Width - Maximum	2.286 mm
Height - Maximum	2.367,2 mm
Dry Weight - Genset (minimum)	25.090 kg
Dry Weight - Genset (maximum)	11.380 kg
Minimum Rating	1.230 kVA
Maximum Rating	1.500 kVA
Rated Speed	1800 rpm

This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.

CAT 3512B Diesel Generator Set

