

CAT 3516 Diesel Generator Set

<https://www.zepelin-powersystems.com/de/en/>



Minimum Rating	1600 kVA
Maximum Rating	2000 kVA
Emissions/Fuel Strategy	Low Fuel Consumption
Voltage	380 to 415 Volts
Frequency	50 Hz
Speed	1500 rpm
Duty Cycle	Standby, Mission Critical, Prime, Continuous
Engine Model	3516 TA, V-16, 4-Stroke Water-Cooled Diesel
Bore	170 mm
Stroke	190 mm
Displacement	69 l
Compression Ratio	13.0:1
Aspiration	TA
Fuel System	Mechanical unit injection
Governor Type	Woodward
Length - Maximum	5.953 mm
Width - Maximum	2.286 mm
Height - Maximum	2.410 mm
Dry Weight - Genset (maximum)	15.350 kg
Maximum Rating	2.000 kVA
Minimum Rating	1.600 kVA
Rated Speed	1500 rpm

This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.

CAT 3516 Diesel Generator Set

