

CAT 3516 Diesel Generator Set

<https://www.zepelin-powersystems.com/de/en/>



Minimum Rating	1450 ekW
Emissions/Fuel Strategy	Low Fuel, Low Emissions
Voltage	380 to 13800 Volts
Frequency	60 Hz
Speed	1800 rpm
Duty Cycle	Standby, Mission Critical, Prime, Continuous
Engine Model	3516 TA, V-16, 4-Stroke Water-Cooled Diesel
Bore	170 mm
Stroke	190 mm
Displacement	69 l
Compression Ratio	13.0:1
Aspiration	TA
Fuel System	Mechanical unit injection
Governor Type	Woodward
Length - Maximum	6.273 mm
Width - Maximum	2.286 mm
Height - Maximum	2.410 mm
Dry Weight - Genset (maximum)	13.080 kg
Maximum Rating	1600 ekW
Maximum Rating	1.600 kVA
Minimum Rating	1.450 kVA
Rated Speed	1800 rpm

This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.

CAT 3516 Diesel Generator Set

