

## CAT 3516B Generator Set

<https://www.zeppelin-powersystems.com/de/en/>



Minimum Rating	1640 ekW
Maximum Rating	2250 ekW
Emissions/Fuel Strategy	Low Fuel, Low Emissions
Voltage	380 to 13800 Volts
Frequency	60 Hz
Speed	1800 rpm
Duty Cycle	Standby, Mission Critical, Prime, Continuous
Engine Model	3516B TA, V-16, 4-Stroke Water-Cooled Diesel
Bore	170 mm
Stroke	190 mm
Displacement	69 l
Compression Ratio	14.0:1 Std 15.5:1 HD
Aspiration	TA
Fuel System	Electronic unit injection
Governor Type	Adem™3
Length - Maximum	6.385 mm
Width - Maximum	2.286 mm
Height - Maximum	2.494 mm
Dry Weight - Genset (maximum)	14.180 kg
Maximum Rating	2.250 kVA
Minimum Rating	1.640 kVA
Rated Speed	1800 rpm

This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.

**CAT 3516B Generator Set**

