

## CAT 3516C Generator Set

<https://www.zeppelin-powersystems.com/de/en/>



Minimum Rating	1650 ekW
Maximum Rating	2500 ekW
Emissions/Fuel Strategy	U.S. EPA Cert., Tier 2
Voltage	380 to 13800 Volts
Frequency	60 Hz
Speed	1800 rpm
Duty Cycle	Standby, Mission Critical, Prime, Continuous
Engine Model	3516C, ATAAC, V-16,4-Stroke Water-Cooled Diesel
Bore	170 mm
Stroke	190 mm
Stroke - HD	215 mm
Displacement	78 l
Compression Ratio	14.7:1
Aspiration	TA
Fuel System	Electronic unit injection
Governor Type	Adem™3
Length - Minimum	7.229 mm
Length - Maximum	7.495 mm
Width - Minimum	2.379 mm
Width - Maximum	2.569 mm
Height - Minimum	2.958 mm
Height - Maximum	3.009 mm
Dry Weight - Genset (minimum)	16.275 kg
Dry Weight - Genset (maximum)	17.590 kg
Rated Speed	1800 rpm
Minimum Rating	1.650 kVA
Maximum Rating	2.500 kVA

**This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.**

## CAT 3516C Generator Set

