

## CAT 3516C Tier 4 Final

<https://www.zeppelin-powersystems.com/de/en/>



Minimum Rating	1650 ekW
Maximum Rating	2500 ekW
Emissions/Fuel Strategy	U.S. EPA Certified
Voltage	480 to 13800 Volts
Frequency	60 Hz
Speed	1800 rpm
Duty Cycle	Standby, Mission Critical, Prime
Engine Model	3516C HD, ATAAC, V-16, 4-Stroke Water-Cooled Diesel
Bore	170 mm
Stroke	215 mm
Displacement	4.764,73 l
Compression Ratio	14.7:1
Aspiration	TA
Fuel System	Electronic unit injection
Governor Type	ADEM™A4
Length - Minimum	6.796,6 mm
Length - Maximum	7.037,5 mm
Width - Minimum	2.378,7 mm
Width - Maximum	2.569 mm
Height - Minimum	2.964,8 mm
Height - Maximum	3.019 mm
Dry Weight - Genset (minimum)	16.874 kg
Dry Weight - Genset (maximum)	18.270 kg
Maximum Rating	2.500 kVA
Minimum Rating	1.650 kVA
Rated Speed	1800 rpm

This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.

**CAT 3516C Tier 4 Final**

