

CAT C18 (SRMP) Marine Generator Set

<https://www.zeppelin-powersystems.com/de/en/>



Minimum Rating	260 ekW (325 kVA)
Maximum Rating	565 ekW (706 kVA)
Frequency	50 hz
Speed	50 Hz - 1500 rpm, 60 Hz - 1800 rpm
Configuration	In-line 6, 4-Stroke-Cycle Diesel
Aspiration	Turbocharged - aftercooled
Bore	145 mm
Stroke	183 mm
Fuel System	MEUI
Emissions	EPA Tier 3, IMO II, EU IW
Height	2.408 mm
Length	4.741 mm
Length	3.038 mm
Height	1.648 mm
Excitation	SRMP
Insulation	Class H
IP Rating	IP23 (standard), IP 44 (optional)
Voltage Regulator	CDVR (Digital Voltage)
Width	1.699 mm
Width	1.411 mm
Weight - Approximate	6.076 kg
Weight - Approximate	4.221 kg
Maximum Rating	706 kVA
Minimum Rating	325 kVA
Rated Speed	50 Hz - 1500 rpm, 60 Hz - 1800 rpm

This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.