

CAT C32 Generator Set

<https://www.zepelin-powersystems.com/de/en/>

Cat® C32, 1500 kVA, 50 Hz
Diesel Generator Set



Up to 6% Power Density Advantage (kVA/m²) vs. Competition



G3 Performance as per ISO 8528-5 load steps



Standard 50°C Radiator Cooling



Up to 14.3% Lighter Than Competitors



Up to 35% Motor Starting Advantage vs. Competition



Full Power for up to 50°C; 1500m/20°C after some competitors begin to derate

LET'S DO THE WORK.



Minimum Rating	910 kVA
Maximum Rating	1500 kVA
Emissions/Fuel Strategy	Low Fuel, Low Emissions
Voltage	400 to 3300 Volts
Frequency	50 Hz
Speed	1500 rpm
Duty Cycle	Standby, Mission Critical, Prime, Continuous
Engine Model	C32 TA, V-12, 4-Stroke Water-Cooled Diesel
Bore	145 mm
Stroke	162 mm
Displacement	32,1 l
Compression Ratio	15.0:1
Aspiration	TA
Fuel System	MEUI
Governor Type	Adem™ A4
Length - Minimum	4.165 mm
Length - Maximum	4.485 mm
Width - Minimum	1.684 mm
Width - Maximum	2.228 mm
Height - Minimum	2.162 mm
Height - Maximum	2.194 mm
Dry Weight - Genset (minimum)	6.668 kg
Dry Weight - Genset (maximum)	8.099 kg
Maximum Rating	1.500 kVA
Minimum Rating	910 kVA
Rated Speed	1500 rpm

This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.

CAT C32 Generator Set

