

CAT C9.3 Marine Generator Set

<https://www.zepelin-powersystems.com/de/en/>



| | |
|-------------------------|--|
| Excitation | Permanent Magnet |
| Minimum Rating | 185R kW (231 kVA) at 50hz, 224R kW (280 kVA) at 60hz |
| Maximum Rating | 250R kW (313 kVA) at 50hz, 300 kW (375 kVA) at 60hz |
| Frequency | 50 Hertz & 60 Hertz |
| Speed | 1500 rpm @ 50Hz & 1800 rpm @ 60Hz |
| Aspiration | Turbocharged Aftercooled |
| Bore | 105 mm |
| Stroke | 135 mm |
| Fuel System | Common Rail |
| Engine Model | C9.3 |
| Emissions/Fuel Strategy | EPA Tier 3, IMO II, EU IW |
| Height | 1.436 mm |
| Length - Engine | 2.170 mm |
| Weight - Approximate | 2.367 kg |
| Width - Engine | 1.260 mm |
| Insulation | Class H |
| Drip Proof | IP23 |
| Voltage Regulator | approx. 0.5% |
| Number of Leads | 12-Lead 2 wires per lead |
| Maximum Rating | 313 kVA |
| Minimum Rating | 231 kVA |
| Rated Speed | 1500 rpm @ 50Hz & 1800 rpm @ 60Hz |

This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.