

CAT Cat® C3.6 Diesel Engine

<https://www.zeppelin-powersystems.com/de/en/>



| | |
|---|--|
| Maximum Power | 100 kW |
| Maximum Torque | 550 Nm @ 1600 rpm |
| Rated Speed | 2000-2400 rpm |
| Minimum Power | 55 kW |
| Emissions | U.S. EPA & CARB Tier 4 Final, EU Stage V |
| Engine Configuration | In-Line 4 |
| Bore | 98 mm |
| Stroke | 120 mm |
| Displacement | 3,6 l |
| Compression Ratio | 17.0:1 |
| Aspiration | Turbocharged-Aftercooled (TA) |
| Combustion System | Direct Injection |
| Rotation from Flywheel End | Counterclockwise |
| Aftertreatment | DOC+DPF or DOC+DPF+SCR |
| Length | 667 mm |
| Width | 564 mm |
| Height | 787 mm |
| Weight - Net Dry - Basic Operating Engine | 381 kg |
| Without Optional Attachments | |

This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.