

CAT Cat® C4.4 Marine Generator Set

<https://www.zeppelin-powersystems.com/de/en/>



Minimum Rating	36.0R ekW (45 kVA)
Maximum Rating	99.0 ekW (123 kVA)
Frequency	50 Hz or 60 Hz
Speed	1500 rpm or 1800 rpm
Engine Model	In-line 4, 4-Stroke-Cycle Diesel
Aspiration	NA, T, TA
Bore	105 mm
Stroke	127 mm
Displacement	4,4 l
Governor Type	Electronic
Emissions/Fuel Strategy	EPA Tier 2 (60 Hz), EU 97/68EC Stage II (50 Hz)
Length	1.750 mm
Width	1.215 mm
Height	1.000 mm
Weight	805 kg (1775 lb) - 1015 kg (2338 lb)
Excitation	Separately excited from auxiliary winding to provide 300% short circuit current up to 10 seconds
Pitch	2/3
Number of Leads	12 lead reconnectable
Insulation	Class H
IP Rating	IP23 water protection (IP44 available for certain models, contact your dealer for information)
Voltage Regulator	Solid state voltage regulator with integral voltage adjustment potentiometer
Maximum Rating	123 kVA
Minimum Rating	45 kVA
Rated Speed	1500 rpm or 1800 rpm

This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.