

## CAT Cat C7.1 Generator Set

<https://www.zeppelin-powersystems.com/de/en/>



Minimum Rating	100 ekW (125 kVA)
Maximum Rating	200 ekW (250 kVA)
Frequency	50 Hz or 60 Hz
Speed	1500 rpm (50 hz) or 1800 rpm (60 hz)
Engine Model	In-line 6, 4-Stroke-Cycle Diesel
Aspiration	TA
Bore	105 mm
Stroke	135 mm
Displacement	7,1 l
Governor Type	Electronic
Fuel System	Common Rail Fuel System
Emissions/Fuel Strategy	EPA Tier 3, IMO II, EU CC2
Width	956 mm
Height	1.263 mm
Weight	1652 -1840 kg, 3634-4026 lb
Length	76.2 in/1935 mm (minimum), 83.3 in/2116 mm (maximum)
Pitch	2/3
Number of Leads	12
Insulation	Class H
IP Rating	IP23 Water protection
Voltage Regulator	Solid state
Maximum Rating	250 kVA
Minimum Rating	125 kVA
Rated Speed	1500 rpm (50 hz) or 1800 rpm (60 hz)

This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.